

Interior Stop Primer

Product properties

Primer and undercoat paint with particularly good blocking properties and excellent coalescence. Minimizes the risk of water-soluble colourants from the surface can discolour the subsequent paint treatment.

- Good blocking properties
- Primer and undercoat
- Matt surface



Labelling



The product is a declared item in the Supply Chain Declaration Portal (SCDP) for New Buildings generation 4.

Product use

For indoor use on untreated wood or previously treated substrates with a risk for penetration from knots, lignin and water-soluble dyes, water guards and nicotine.

Penetration from knots is a natural phenomenon that in some cases cannot be blocked.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Water blotches, nicotine and soot must be cleaned with Fluren 49.

Sand hard, slippery surfaces flat.

Cracks, unevenness and holes must be filled.

Apply twice for best results.

Application

Brush or roller.

Decide your choice of tool/utensil depending on the finish.

Apply wet on wet and finish by brushing/rolling in the same direction.

Cold/heat can affect the viscosity of the material.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Semi-matt, covered surface.

Finish treatment with paint in desired gloss and colour.

Please note!

If an airless sprayer is used, there is a risk of nozzle stoppage and clogging of filters, hoses and pumps unless these are completely cleaned of other material.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost-free, and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Priming paint
Gloss	Semi Matte
Density (kgs/l)	1.26
Solids Weight %	50
Solids Vol. %	37
Nominal spreading rate (m ² /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Metal Pro Cleaner

Current TDS Version

December 2024

Replaces TDS Version

November 2024